

Primer

Spraykontakt

Sprayable special bonding course for gypsum plaster on concrete.

Material Properties Ready-to-use, quick-drying, orange-pigmented, highly alkali-resistant.

Substrate Primer to promote adhesion and reduce the absorbency of the substrate.

- To avoid differences in colour, a homogeneous substrate must be created with regard to material and drying.
- Not suitable for horizontal surfaces.
- Do not apply to damp or dirty surfaces.

Consumption ca. 0,1 l/m² per coat

Technical Data

- **Type** // fine-rough primer
- **Consistency** // liquid
- **Binder** // modified polymer dispersion
- **Density** // ca. 1,1 g/cm³

Application Stir thoroughly with a slow-speed agitator. Apply Spraykontakt undiluted. Application with a spray gun, roller or brush.

Clean tools with water immediately after use. Carefully cover neighbouring surfaces. Wash off splashes immediately with plenty of water. Do not use at air and building structure temperatures below +5°C or in direct sunlight, draughts or expected night frosts.



Surface procurement After sufficient drying (at least 24 hours at 20°C), coat with mineral or pasty finishing plasters, as well as gypsum-based plasters.

Packaging • 10 l/pail • 40 pail/pallet

Storage Store the pail tightly closed in a cool and frost-free place.

Primer

Spraykontakt

Please note Protect eyes and skin.
Giscode BSW20

Advisory service The information in this data sheet only represents general guidelines. If you have any technical questions regarding a specific application, please contact our sales office.

Visual appearance Fine-rough

Colours Orange

Options

All information in this publication is based on experience, tests and trials. A guarantee for the general validity of individual data and statements is excluded with regard to different processing and construction site conditions. The generally recognised and technical rules of construction technology as well as the applicable standards and guidelines must be observed. The publication of this publication renders previous editions invalid. We reserve the right to make changes in the context of further product and application technology developments. Please refer to our Internet pages for the latest information. Our current terms and conditions of sale and delivery apply to all business transactions.

Safety data sheet available on request.

huma farben GmbH
Ziegelfeldstraße 66
D-73563 Mögglingen
T +49 7174 898990

F +49 7174 8989918
www.huma-farben.de
info@huma-farben.de