

Primer

# Hydro Tiefgrund LF

**Deeply penetrating and hydrophilizing special primer for interior and exterior use.**

**Material Properties** Suitable for porous, absorbent substrates, consolidating and levelling.

**Substrate** Primer to promote adhesion and reduce the absorbency of the substrate.

- To avoid differences in colour, a homogeneous substrate must be created with regard to material and drying.
- Not suitable for horizontal surfaces.
- Do not apply to damp or dirty surfaces.

**Consumption** ca. 0,15–0,25 l/m<sup>2</sup> per coat

**Technical Data**

- **Type** // fine-rough primer
- **Consistency** // liquid
- **Binder** // modified polymer dispersion, hydrosol
- **Density** // ca. 1,0 g/cm<sup>3</sup>

**Application** Stir thoroughly with a slow-speed agitator. Apply Hydro-Tiefgrund LF depending on the condition of the substrate. For critical substrates, the application must be specially tested. Application with a roller or brush.

Clean tools with water immediately after use. Carefully cover neighbouring surfaces. Wash off splashes immediately with plenty of water. Do not use at air and building structure temperatures below +5°C or in direct sunlight, draughts or expected night frosts.



**Surface procurement** After sufficient drying (at least 24 hours at 20°C), coat with mineral or paste-like finishing plasters.

**Packaging** • 10 l/pail • 40 pails/pallet

**Storage** Keep canister and can tightly closed in a cool and frost-free place.

Primer

# Hydro Tiefgrund LF

---

**Please note** Protect eyes and skin.  
Giscode BSW20

---

**Advisory service** The information in this data sheet only represents general guidelines. If you have any technical questions regarding a specific application, please contact our sales office.

---

## Visual Appearance

---

**Colours** transparent

---

## Options

---

All information in this publication is based on experience, tests and trials. A guarantee for the general validity of individual data and statements is excluded with regard to different processing and construction site conditions. The generally recognised and technical rules of construction technology as well as the applicable standards and guidelines must be observed. The publication of this publication renders previous editions invalid. We reserve the right to make changes in the context of further product and application technology developments. Please refer to our Internet pages for the latest information. Our current terms and conditions of sale and delivery apply to all business transactions.

---

Safety data sheet available on request.

**huma farben GmbH**  
Ziegelfeldstraße 66  
D-73563 Mögglingen  
T +49 7174 898990

F +49 7174 8989918  
www.huma-farben.de  
info@huma-farben.de