

Primer

Aufbrennsperre 84

Primer for interior use to regulate absorbency.

Material Properties Concentrate, non-film-forming, hydrophobizing, for short-term plastering work.

Substrate Primer to promote adhesion and reduce the absorbency of the substrate.

- To avoid differences in colour, a homogeneous substrate must be created with regard to material and drying.
- Not suitable for horizontal surfaces.
- Do not apply to damp or dirty surfaces.

Consumption ca. 0,15 l/m² per coat

Technical Data

- **Type** // primer
- **Consistency** // liquid
- **Density** // ca. 1,0 g/cm³

Application Stir the pail well before starting work. Dilute Aufbrennsperre 84 according to the substrate and apply or spray evenly with a lambskin roller/brush to cover the entire surface. Clean tools with water immediately after use. If possible, wipe off soiling caused by the Aufbrennsperre (splashes or similar) from the contaminated surfaces with warm water while still fresh.

Dried material can be removed after softening with a wet wipe or similar. Wait with subsequent work until Aufbrennsperre 84 is no longer sticky and is completely dry (at least 6 hours at 20 °C and 65% relative humidity). In cool and damp building site conditions, the drying times are correspondingly longer.

- Brick masonry // 1:2–1:6
- Sand-lime brickwork // 1:6
- Autoclaved aerated concrete masonry (gas concrete) // 1:2–1:4



Surface procurement After sufficient drying (at least 24 hours at 20°C), coat with mineral or pasty finishing plasters, as well as gypsum-based plasters.

Packaging

- 10 l/canister
- 40 canisters/pallet

Storage Store the pail tightly closed in a cool and frost-free place.

Please note Protect eyes and skin.
Giscode BSW20

Primer

Aufbrennsperre 84

Advisory service

The information in this data sheet only represents general guidelines. If you have any technical questions regarding a specific application, please contact our sales office.

Visual appearance

Colours opaque

Options

All information in this publication is based on experience, tests and trials. A guarantee for the general validity of individual data and statements is excluded with regard to different processing and construction site conditions. The generally recognised and technical rules of construction technology as well as the applicable standards and guidelines must be observed. The publication of this publication renders previous editions invalid. We reserve the right to make changes in the context of further product and application technology developments. Please refer to our Internet pages for the latest information. Our current terms and conditions of sale and delivery apply to all business transactions.

Safety data sheet available on request.

huma farben GmbH
Ziegelfeldstraße 66
D-73563 Mögglingen
T +49 7174 898990

F +49 7174 8989918
www.huma-farben.de
info@huma-farben.de