

easy Bio Streichputz G 0,5 / extra 1.0

Super-light mineral plaster for interior use. Ready-to-use, breathable, for a healthy indoor climate.

Material Properties Preservative-free, solvent- and plasticizer-free, fiber-reinforced.

Substrate As a finishing plaster on substrates made of

- Concrete
- Lime and lime-cement plasters of categories CSII, CS III and CS IV (previously MG P II and P III)
- mineral reinforcement or levelling plaster layer

All substrates must be dry, sound, clean and free of adhesion-reducing residues.

Consumption **G 0,5 (fine)** // ca. 0.5 mm / 0,15 kg/m² (per coat)
extra 1.0 // ca. 1.0 mm / 0,3 kg/m² (per coat)

Technical Data

- **Classification** // Interior plaster with organic binders
- **Density** // ca. 1,2 kg/dm³
- **Tensile strength** // >= 0,3 MPas according to EN 1542
- **Water vapour permeability S_d** // Class 1 (high) according to EN ISO 7783-2

CE	DIN EN 15824 Plaster with organic binders for interior use	Durability (frost resistance) NPD
	11	Water vapour permeability V1 high
huma farben GmbH D-73563 Mögglingen	Water absorption NPD	Reaction to fire B-s1, d0
	Tensile strength >= 0,3 N/mm ²	Product Interior plaster

Application



Material is ready for use after brief stirring with a slow-speed agitator. If necessary, adjust consistency with a little water. Apply plaster with a roller, brush or spraying device.

Clean tools with water immediately after use. To avoid build-up and structural defects, work quickly wet-on-wet and use sufficient labour for larger areas. On contiguous surfaces, only use material with the same batch number or mix materials with different batch numbers beforehand. Carefully cover neighbouring areas. Wash off splashes immediately with plenty of water. Do not use at air and building structure temperatures below +5°C.

Attention should be paid to:

VOB, Part C, DIN 18363, Sections 2 and 3, as well as the BFS data sheets for the relevant work areas.

Interior plasters

easy Bio Streichputz G 0,5 / extra 1.0

Packaging

- 16 kg/pail
- 24 pails/pallet

Storage

Store the pail tightly closed in a cool and frost-free place.

Please note

Protect eyes and skin.
Giscode BSW20

Advisory service

The information in this data sheet only represents general guidelines. If you have any technical questions regarding a specific application, please contact our sales office.

Visual Appearance

Fine rough

Colours

White

All information in this publication is based on experience, tests and trials. A guarantee for the general validity of individual data and statements is excluded with regard to different processing and construction site conditions. The generally recognised and technical rules of construction technology as well as the applicable standards and guidelines must be observed. The publication of this publication renders previous editions invalid. We reserve the right to make changes in the context of further product and application technology developments. Please refer to our Internet pages for the latest information. Our current terms and conditions of sale and delivery apply to all business transactions.

Safety data sheet available on request.

huma farben GmbH
Ziegelfeldstraße 66
D-73563 Mögglingen
T +49 7174 898990

F +49 7174 8989918
www.huma-farben.de
info@huma-farben.de