

X-treme line

HIGH PERFORMANCE SPRAY MARKING SYSTEM

Premium direct colour with Light Reflection formula for perfect stadium lines.

Material Properties	Ready-to-use, quick-drying premium direct paint with optimum atomisation. Suitable for professional marking equipment with hollow cone or airless nozzle. Made from >97% natural raw materials.	
Coating build-up	Always use direct colour undiluted.	
Consumption	Approx. 2.5 - 5 litres per football pitch, depending on the nozzle used.	
Technical Data	<ul style="list-style-type: none"> • Composition // Polymer dispersion, micronized titanium dioxide, additives, water. • Density // ca. 1,15 g/cm³ • Gloss level // dull matt 	
Application	On dry and damp sports fields. Shake canister well before use. Rinse filter and nozzle with water after use.	
Material description	<p>A very environmentally friendly, extra-white professional product for line marking on sports pitches, lawns, artificial turf and hard courts.</p> <ul style="list-style-type: none"> • Particularly high rain resistance, no stamping • LIGHT REFLECTION FORMULA • Excellent adhesion • ultra-white • Environmentally and plant-friendly • Lawn growth is not impaired • Groundwater neutral • solvent-free • Low odour 	
Drying	Fast drying. Drying time is extended at low temperatures and high humidity.	
Packaging	5 litre canister	<ul style="list-style-type: none"> • 2 canisters / parcel • 10 canisters / pallet • 20 canisters / pallet • 40 canisters / pallet
Storage	Store the canister tightly closed in a cool and frost-free place.	
Please note	Protect eyes and skin. Giscode: BSW20	
Advisory service	The information in this data sheet only represents general guidelines. If you have any technical questions regarding a specific application, please contact our sales office.	
Gloss level	dull matt	

Specialty products

X-treme line

Colours

white

All information in this publication is based on experience, tests and trials. A guarantee for the general validity of individual data and statements is excluded with regard to different processing and construction site conditions. The generally recognised and technical rules of construction technology as well as the applicable standards and guidelines must be observed. The publication of this publication renders previous editions invalid. We reserve the right to make changes in the context of further product and application technology developments. Please refer to our Internet pages for the latest information. Our current terms and conditions of sale and delivery apply to all business transactions.

Safety data sheet available on request.

huma farben GmbH
Ziegelfeldstraße 66
D-73563 Mögglingen
T +49 7174 898990

F +49 7174 8989918
www.huma-farben.de
info@huma-farben.de